

EZwindow 221 :E



EZwindow 121 :BT :E :IECC



The 221 and 121 EZwindow configurations are available for special applications. **For general capabilities of the EZwindow products, please refer to the EZwindow brochure.**

## EZwindow™ 121 Video Processor

EZwindow 121 is identical to a EZwindow-2 with the following differences. EZwindow 121:

- Offers optional NTSC composite output with BNC (:CB)
- Offers optional composite / component output with BNC pigtail cabling (:CC)
- Offers optional Benchtop enclosure (:BT)

## EZwindow 121 Ordering Configurations

EZwindow 121	standard 1U rackmount enclosure
EZwindow 121 :E	with Ethernet interface
EZwindow 121 :BT	Benchtop enclosure (comes with feet)
EZwindow 121 :CB	Composite output with BNC connector
EZwindow 121 :CC	Composite / Component output with pigtail cable with RCA terminations
EZwindow 121 :IECC	with IEC power retention clip

Options may be combined. For example, the following are all valid ordering configurations:

- EZwindow 121 :BT :CB
- EZwindow 121 :BT :CB :E
- EZwindow 121 :BT :CC
- EZwindow 121 :BT :CC :E

## EZwindow™ 221 Video Processor

EZwindow 221 is identical to qty (2) EZwindow-2 units with the following differences. EZwindow 221:

- Fits in 1U of rackspace whereas (2) EZwindow-2's require 2U of rackspace
- Offers optional NTSC composite output with BNC (:CB)
- Offers optional composite / component output with BNC pigtail cabling (:CC)

## EZwindow 221 Ordering Configurations

EZwindow 221	standard 1U rackmount enclosure
EZwindow 221 :E	with Ethernet interfaces
EZwindow 221 :CB	Composite output with BNC connector
EZwindow 221 :CC	Composite / Component output with pigtail cable with BNC terminations
EZwindow 221 :IECC	with IEC power retention clip

Options may be combined. For example, the following are all valid ordering configurations:

- EZwindow 221 :CB
- EZwindow 221 :CB :E
- EZwindow 221 :CC
- EZwindow 221 :CC :E

Electro Mechanical	Specification
Input Power	IEC Connector, 100-240 VAC, 47-63 Hz, less than 60 Watts
Dimensions (W x D x H)	1U Rackmount: 19"W x 13.75"D x 1.75"H BT 10.5"Wx10.75"Dx1.95"H (2.375" w/ ft)
Weight	Less than 7 lbs.

Electro Mechanical	Specification
Input Power	IEC Connector, 100-240 VAC, 47-63 Hz, less than 60 Watts
Dimensions (W x D x H)	1U Rackmount: 19" x 13.75" x 1.75"
Weight	Less than 7 lbs.